

Monobloc Aluminum Fire Extinguishers



***Light Weight
Seamless
Corrosion Free***



IS:15683



Thanks to a switch over to aluminium body, new Shootfire extinguisher is lighter and thus more portable. So you spend fewer minutes in carrying the extinguisher to the fire and fighting it successfully.

There's more to it than meets the eye. The new aluminum cylinders are produced by the extrusion method, rather than the spinning of steel pipes. This leaves no room for leakage or tampering. The result is an extinguisher that is not only lighter, but also sturdier and corrosion free.

FOAM BASED FIRE EXTINGUISHERS (ALUMINIUM)

FOAM BASED STORED PRESSURE TYPE FIRE EXTINGUISHERS

FIRE EXTINGUISHER CAPACITIES	6lt.	9lt.
MINIMUM PERIOD FOR WHICH THROW OF JET MAINTAINED	15 sec	25 sec
MAXIMUM PERIOD TO DISCHARGE ATLEAST 90% OF CONTENTS	40 sec.	60 sec
RANGE OF JET	3 mtr.	6 mtr.
EMPTY. WT. (APPROX)	1.8 kg	3.2 kg
FULL WT. (APPROX)	7.8 kg	12.2 kg
FIRE RATING	2A, 34B	4A, 89B
WORKING PRESSURE	15 KGF/CM ²	15 KGF/CM ²
HYDRO PRESSURE	35 KGF/CM ²	35 KGF/CM ²
BURSTING PRESSURE	55 KGF/CM ²	55 KGF/CM ²

Approvals:  IS:15683  



WATER BASED FIRE EXTINGUISHERS (ALUMINIUM)

WATER BASED STORED PRESSURE TYPE FIRE EXTINGUISHERS

FIRE EXTINGUISHER CAPACITIES	6lt.	9lt.
MINIMUM PERIOD FOR WHICH THROW OF JET MAINTAINED	20 sec	60 sec
MAXIMUM PERIOD TO DISCHARGE ATLEAST 90% OF CONTENTS	50 sec	120 sec
RANGE OF JET	3 mtr.	6 mtr.
EMPTY. WT. (APPROX)	1.8 kg.	3.2 kg.
FULL WT. (APPROX)	7.8 kg.	12.2 kg.
FIRE RATING	2A	3A
WORKING PRESSURE	15 KGF/CM ²	15 KGF/CM ²
HYDRO PRESSURE	35 KGF/CM ²	35 KGF/CM ²
BURSTING PRESSURE	55 KGF/CM ²	55 KGF/CM ²

Approvals:  IS:15683  



CLEAN AGENT GAS BASED FIRE EXTINGUISHERS (ALUMINIUM)

CLEAN AGENT STORED PRESSURE TYPE FIRE EXTINGUISHERS

FIRE EXTINGUISHER CAPACITIES	2kg.	4kg.	6kg.
MINIMUM PERIOD FOR WHICH THROW OF JET MAINTAINED	8 sec	16 sec	20 sec
MAXIMUM PERIOD TO DISCHARGE ATLEAST 90% OF CONTENTS	16 sec	20 sec	25 sec
RANGE OF JET	2 mtr.	2 mtr.	2 mtr.
EMPTY. WT. (APPROX)	0.8 KG	1.6 KG	2.0 KG
FULL WT. (APPROX)	2.8 KG	5.6 KG.	9.0 KG.
FIRE RATING	8B	1A, 13B	2A, 21B
WORKING PRESSURE	15KGF/CM ²	15KGF/CM ²	15KGF/CM ²
HYDRO PRESSURE	35KGF/CM ²	35KGF/CM ²	35KGF/CM ²
BURSTING PRESSURE	55KGF/CM ²	55KGF/CM ²	55KGF/CM ²

Approval:

EN3.7



IS:15683

GAS: DUPONT™ FE36™ Clean Agent



POWDER BASED FIRE EXTINGUISHER (ALUMINIUM)

ABC STORED PRESSURE TYPE FIRE EXTINGUISHER.

FIRE EXTINGUISHER CAPACITIES	1 KG	2 KG	4 KG	6 KG	9 KG
MINIMUM PERIOD FOR WHICH THROW OF JET MAINTAINED	8 SEC	8 SEC	16 SEC	20 SEC	25 SEC
MAXIMUM PERIOD OF DISCHARGE ATLEAST 90% OF CONTENTS	12 SEC	16 SEC	20 SEC	25 SEC	30 SEC
RANGE OF JET	2 MTR.	3 MTR.	4 MTR.	6 MTR.	7 MTR.
EMPTY. WT. (APPROX)	0.55 KG	0.7 KG	1.5 KG.	1.8 KG.	3.2 KG
FULL WT. (APPROX)	1.55KG.	2.7 KG.	5.5 KG.	7.8 KG.	12.2 KG.
FIRE RATING	1A, 8B	1A, 8B	2A, 34B	4A, 55B	6A, 89B
WORKING PRESSURE	15 KGF/CM ²	15 KGF/CM ²	15 KGF/CM ²	15 KGF/CM ²	15 KGF/CM ²
HYDRO PRESSURE	35 KGF/CM ²	35 KGF/CM ²	35 KGF/CM ²	35 KGF/CM ²	35 KGF/CM ²
BURSTING PRESSURE	55 KGF/CM ²	55 KGF/CM ²	55 KGF/CM ²	55 KGF/CM ²	55 KGF/CM ²

Approval:



IS:15683



Contact Details

Registered Office

Vimal Fire Controls Pvt. Ltd.

19/20, Vardhaman Complex, L. B. S Marg,
Opposite 24/7 Corporate Park, Behind
Punjab & Sindh Bank, Vikhroli - West,
Mumbai - 400083, Maharashtra, India

Ph.: +91 22 42010101 / 25783335 / 36 / 37

Fax: +91 22 25783338 | +91 22 25782655

Email Address: vfcplmumbai@vimalfire.com

www.vimalfire.com

